

BUILT FOR WHEN THE PRESSURE IS ON

Built for long-term use to provide maximum productivity, Bobcat large air compressors are designed for big jobs like general construction, mining and abrasive blasting. With heavy-duty construction and highly innovative features, these compressors maximize productivity.

PA825V

This two-in-one portable air compressor delivers dual pressures with airflow ranging from 750 to 825 cfm and pressure ranging from 125 to 150 psi.

INTUITIVE MACHINE DIAGNOSTICS

Ensure easy serviceability and lower cost of ownership.

BOBCAT-TOUGH CONSTRUCTION

One look at the robust drawbar, axles and steel enclosure, and you can see this machine is built to last.

PUSH-BUTTON PRESSURE CONTROL

Easily switch from low to high pressure at the push of a button.

THERMOSTATIC COOLING FAN

Reduces noise levels and your fuel costs.

100-GALLON FUEL TANK

Get nine productive hours of runtime.

EFFICIENT AIREND

Demands less horsepower for high-volume cfm output.

PA915

This hard-working, heavy-duty air compressor offers the best servicing capabilities in the industry, maximizing uptime in harsh operating conditions.

EASY MAINTENANCE

Unparalleled serviceability includes centralized fluid drain locations and simple access to all service components.

DETAILED CONTROL PANEL

Includes more pre-loaded resources than any other model.

NINE HOURS OF RUNTIME

In a powerful yet surprisingly compact unit.

PATENTED IQ SYSTEM

Precisely meet ISO standards for your industry with instrument-quality air and zero-discharge condensate removal.



Model	PA825V	PA915
COMPRESSOR ROTARY SCREW/SINGLE STAGE		
Free-Air Delivery (low/high)	825/750 cfm (23.4/21.2 m ³ /min.)	915 cfm (25.9 m ³ /min.)
Rated Operating Pressure (low/high)	125/150 psig (8.6/10.3 bar)	150 psig (10.3 bar)
Pressure Range	80–175 psig (5.5–12.1 bar)	80–175 psig (5.5–12.1 bar)
Air Discharge Outlet NPT Size	2.0 in. (50 mm)	2.0 in. (50 mm)
Air Discharge Outlet Quantity	1	1
Fuel Tank Capacity	100 gal. (379 L)	128 gal. (485 L)
ENGINE		
Make & Model	Cummins QSB6.7	Cummins B6.7
Emissions Tier Level	Tier 4 Final (T4F)	Tier 4 Final (T4F)
Number of Cylinders	6	6
Displacement	408 cu. in. (6.7 L)	408 cu. in. (6.7 L)
Rated Speed (low/high)	2100/1935 rpm	1800 rpm
Idle Speed	1300 rpm	1200 rpm
Bhp @ Rated Speed (low/high)	266/262 Bhp (198/195 kW)	298 Bhp (222 kW)
Electrical	24V	24V
Hours of Operation @ Full Load (low/high)	9.1/9.3 hr.	9.2 hr.
DIMENSIONS WITH RUNNING GEAR		
Length	203.3 in. (5164 mm)	226.6 in. (5748 mm)
Width	90.2 in. (2291 mm)	82.6 in. (2098 mm)
Height	88.5 in. (2248 mm)	101.3 in. (2573 mm)
Track Width	80.3 in. (2040 mm)	69.3 in. (1760 mm)
Tire Size	15.0 in. (381 mm)	16.0 in. (406 mm)
Shipping Weight (without fuel)	8620 lb. (3910 kg)	9789 lb. (4440 kg)
Working Weight (with fuel)	9330 lb. (4230 kg)	10,692 lb. (4849 kg)
DIMENSIONS WITHOUT RUNNING GEAR		
Length	152.4 in. (3871 mm)	171.0 in. (4343 mm)
Width	80.6 in. (2047 mm)	83.0 in. (2108 mm)
Height	79.0 in. (2007 mm)	95.0 in. (2413 mm)
Shipping Weight (without fuel)	7840 lb. (3560 kg)	8642 lb. (3920 kg)
Working Weight (with fuel)	8550 lb. (3880 kg)	9855 lb. (4470 kg)